


# Plafon Slim GI



Dimensiones Redondo		
	B	C
12W	28mm	Ø168mm
18W	28mm	Ø210mm
24W	28mm	Ø285mm



Dimensiones Cuadrado			
	A	B	C
12W	28mm	168mm	168mm
18W	28mm	210mm	210mm
24W	28mm	285mm	285mm



Código	Modelo	Potencia	Temperatura de Color	Flujo Luminoso	Código de Barras	Caja
90097	SUPERFICIAL CUADRADO	12W	3000K	730lm	4897082823308	20 unid.
90606	SUPERFICIAL CUADRADO	12W	4000K	730lm	4897082825470	20 unid.
90098	SUPERFICIAL CUADRADO	12W	6000K	730lm	4897082823315	20 unid.
90607	SUPERFICIAL CUADRADO	18W	3000K	1200lm	4897082825487	20 unid.
90608	SUPERFICIAL CUADRADO	18W	4000K	1200lm	4897082825494	20 unid.
90609	SUPERFICIAL CUADRADO	18W	6000K	1200lm	4897082825500	20 unid.
90099	SUPERFICIAL CUADRADO	24W	3000K	1600lm	4897082823322	10 unid.
90610	SUPERFICIAL CUADRADO	24W	4000K	1600lm	4897082825517	10 unid.
90100	SUPERFICIAL CUADRADO	24W	6000K	1600lm	4897082823339	10 unid.
90101	SUPERFICIAL REDONDO	12W	3000K	730lm	4897082823346	20 unid.
90611	SUPERFICIAL REDONDO	12W	4000K	730lm	4897082825524	20 unid.
90102	SUPERFICIAL REDONDO	12W	6000K	730lm	4897082823353	20 unid.
90612	SUPERFICIAL REDONDO	18W	3000K	1200lm	4897082825531	20 unid.
90613	SUPERFICIAL REDONDO	18W	4000K	1200lm	4897082825548	20 unid.
90614	SUPERFICIAL REDONDO	18W	6000K	1200lm	4897082825555	20 unid.
90103	SUPERFICIAL REDONDO	24W	3000K	1600lm	4897082823360	10 unid.
90615	SUPERFICIAL REDONDO	24W	4000K	1600lm	4897082825562	10 unid.
90104	SUPERFICIAL REDONDO	24W	6000K	1600lm	4897082823377	10 unid.

MULTIVOLTAJE  
100-240V~VIDA ÚTIL (L70)  
25.000hÁNGULO DE  
APERTURA 110°GRADO DE PROTECCIÓN  
IP20\*

\*Protegido contra objetos sólidos con Ø mayor que 12mm. No protegido contra el agua.